

Transport containers Successful concept for maximum efficiency

Avermann transport containers are used optionally with static compactors or screw compactors.

Moreover, they can easily be integrated into shifting units. Depending on the application and type of static or screw compactor, different container sizes from 20 m³ to 32 m³ are available.

Avermann Maschinenfabrik GmbH & Co. KG Lengericher Landstraße 35 49078 Osnabrück . Germany

Phone +49 5405 505 - 0 . Telefax +49 5405 6441 info@avermann.de . www.avermann.de



Transport containers Technical data



Transport containers at static compactor facility

Options

You specify the details – for an optimal set-up:

Use with static compactors and screw compactors

Your benefits:

- Capacity: Net capacity up to 32 m³
- Locking options: Side-hinged or top-hinged rear door with various locking mechanisms
- > Tailor-made: Need-based use
- > Stable: Sturdy steel construction for long life

Overview of technical data	SP-B-20	SP-B-22	SP-B-25	SP-B-28	SP-B-30	SP-B-32
Net capacity	20 m³	22 m³	25 m³	28 m³	30 m³	32 m³
Machine length	5,030 mm	5,480 mm	6,130 mm	6,780 mm	7,130 mm	7,350 mm
Machine width	2,495 mm					
Machine height	2,600 mm					
Weight empty	2,900 kg	3,100 kg	3,370 kg	3,600 kg	3,760 kg	3,800 kg

Special containers on request