



Avermann

Wet waste compactors for chain lift and hook lift trucks

Solutions for hygienic wet waste disposal

Avermann offers special compactors for the reliable compaction of wet waste materials.

They are the ideal solution for wet waste materials, such as arising in hotels, canteen-kitchens, rest homes or hospitals. Due to the efficient Avermann 4-point locking your compactor is absolutely liquid-tight. The self-cleaning press ram and the tub-shaped design of the press head ensure low-maintenance operation. Avermann wet waste compactors are available with a pre-defined standard design suitable for the Exchange route process.

Avermann
Maschinenfabrik GmbH & Co. KG
Lengericher Landstraße 35
49078 Osnabrück . Germany

Phone +49 5405 505 - 0 . Telefax +49 5405 6441
info@avermann.de . www.avermann.de



Wet waste compactors for chain lift and hook lift trucks

Wet waste compactors for chain lift and hook lift trucks

Technical data

Options

You specify the details – for an optimal setup:

- › Feed opening cover
- › Ozone generator
- › Rear door with all-around seal
- › 4-point-locking (optionally with extended locking ratchet)
- › Web-based message system to check location and filling levels
- › C-pipe connections

Your benefits:

- › **Clean:** Liquid-tight for hygienic disposal
- › **Durable:** Robust construction for long lifetime
- › **Reliable:** 24V safety and digital control
- › **Optimized:** Large maintenance door

Standard RAL-colors: ◆ RAL 1003 ◆ RAL 2000 ◆ RAL 3001 ◆ RAL 3020 ◆ RAL 5005 ◆ RAL 5007
◆ RAL 5010 ◆ RAL 5015 ◆ RAL 5017 ◆ RAL 6002 ◆ RAL 6018 ◆ RAL 6024 ◆ RAL 7016 ◆ RAL 7032
◆ RAL 7038 ◆ RAL 9002 *Further RAL colors available on request against surcharge.*



External hydraulic cylinder



Ozon generator

Technical data

	MPC 10 P/E/N/B	MPC 16 P/E/N/B	MPC 20 P/E/N/B
Net capacity	10 m ³	16 m ³	20 m ³
Machine length	4,550 mm	5,490 mm	6,330 mm
Machine width	2,040 mm	2,500 mm	2,500 mm
Machine height	2,510 mm	2,550 mm	2,550 mm
Feed-opening length	1,320 mm	1,320 mm	1,320 mm
Feed-opening width	1,430 mm	1,430 mm	1,430 mm
Feeding height	1,420 mm	1,490 mm	1,490 mm
Dead weight	3,100 kg	3,900 kg	4,100 kg
Oil quantity	45 l	45 l	45 l
Capacity per drive stroke	0.5 m ³	0.5 m ³	0.5 m ³
Cycle time (idle)	22 s	22 s	22 s
Transport system	chain lift	hook lift	hook lift
Drive capacity	5.5 kW	5.5 kW	5.5 kW
Press force	200 kN	200 kN	200 kN

Valid for all machine types:

Electricity: 3 x 400V, N, PE/50 Hz; Plug connector: CEE-5 x 32A/6 h; Fuse protection (on site): 25 A, slow; Control voltage: 24V DC