



# Avermann



## Transport containers

Successful concept for maximum efficiency

**Avermann transport containers are used optionally with static compactors or screw compactors.**

Moreover, they can easily be integrated into shifting units. Depending on the application and type of static or screw compactor, different container sizes from 20 m<sup>3</sup> to 32 m<sup>3</sup> are available.

## Options

**You specify the details – for an optimal set-up:**

- Use with static compactors and screw compactors

**Your benefits:**

- + **Capacity:** Net capacity up to 32 m<sup>3</sup>
- + **Locking options:** Side-hinged or top-hinged rear door with various locking mechanisms
- + **Tailor-made:** Need-based use
- + **Stable:** Sturdy steel construction for long life

## Avermann transport container



*Transport containers at static compactor facility*

Technical data	SP-B-20	SP-B-22	SP-B-25	SP-B-28	SP-B-30	SP-B-32
Net capacity	20 m <sup>3</sup>	22 m <sup>3</sup>	25 m <sup>3</sup>	28 m <sup>3</sup>	30 m <sup>3</sup>	32 m <sup>3</sup>
Machine length	4.890 mm	5.480 mm	5.950 mm	6.570 mm	7.100 mm	7.200 mm
Machine width	2.495 mm	2.495 mm	2.495 mm	2.495 mm	2.495 mm	2.495 mm
Machine height	2.600 mm	2.600 mm	2.600 mm	2.600 mm	2.600 mm	2.600 mm
<b>Weight empty</b>	<b>2.900 kg</b>	<b>3.200 kg</b>	<b>3.400 kg</b>	<b>3.600 kg</b>	<b>3.830 kg</b>	<b>4.430 kg</b>

*Special containers on request*

### **Valid for all machine types:**

Available in all standard RAL colors, other RAL colors on request.