



Avermann



Waste compactors for hook lift trucks

Optimum disposal for high efficiency

Avermann waste compactors reduce household and industrial waste volumes as well as paper and other recyclable fractions to 1/6 of the original volume and thus reduce transport and disposal costs extraordinarily economical. Furthermore, additional costs incurred in open waste and recycling containers by scattered paper, the crushing of boxes, the shredding of bulky boxes etc., are completely eliminated here.

Options

You specify the details – for an optimal setup:

- Slanted or high side walls, individual feed opening possibilities
- Enlarged feed opening “L”
- Top-hinged or side-hinged rear door
- Integrated bin lifter
- Web-based message system
- WasteManagementTeleatics360
- Suitable for stand-alone and ramp installations
- Integrated rear hook

Ihre Vorteile:

- + **High-performance:** 380 kN press force
- + **Reliable:** 24V safety and digital control
- + **User friendly:** Conical container design for easy discharge
- + **Capacious:** Large feed opening
- + **High quality:** Teflon guided press ram and apron plate
- + **Optimized:** Large maintenance door

Avermann Maschinenfabrik GmbH & Co. KG

Lengericher Landstr. 35 • 49078 Osnabrück • Germany • T +49 5405 505-0 • F +49 5405 6441 • E info@avermann.de



Integrated rear hook



Mounted bin lifter

Technical data	MPC 16 P/E/L/R	MPC 18 P/E/L/R	MPC 20 P/E/L/R	MPC 24 P/E/L/R
Net capacity	16 m ³	18 m ³	20 m ³	24 m ³
Machine length*	6.000 mm	6.450 mm	6.800 mm	7.350 mm
Machine width	2.500 mm	2.500 mm	2.500 mm	2.500 mm
Machine height	2.550 mm	2.550 mm	2.550 mm	2.550 mm
Feed-opening length	1.300 mm	1.300 mm	1.300 mm	1.300 mm
Feed-opening width	1.980 mm	1.980 mm	1.980 mm	1.980 mm
Feeding height	1.480 mm	1.480 mm	1.480 mm	1.480 mm
Dead weight	5.100 kg	5.300 kg	5.700 kg	6.200 kg
Oil quantity	70 l	70 l	70 l	70 l
Capacity per drive stroke	1,9 m ³	1,9 m ³	1,9 m ³	1,9 m ³
Cycle time (idle)	63 s	63 s	63 s	63 s
Drive capacity	5,5 kW	5,5 kW	5,5 kW	5,5 kW
Press force	380 kN	380 kN	380 kN	380 kN

*with rear hook: + approx. 260mm

Valid for all machine types:

Electricity: 3 x 400V, N, PE/50 Hz; Plug connector: CEE-5 x 32A/6h; Fuse protection (on site): 25 A, slow; Control voltage: 24 V DC. Available in all standard RAL colors, other RAL colors on request.

Perfectly suitable to compact:

- ✓ Paper
- ✓ Cardboard
- ✓ Foil
- ✓ PET
- ✓ Foam
- ✓ Residual waste
- ✓ Plastic
- ✓ Cans
- ✓ Fruitcrates
- ✓ Styrofoam
- ✓ Textiles
- ✓ Hygiene products
- ✓ Substitute fuels

Optionally with Telematik

